

HARDWALL KERBSIDE HOSE

Hardwall Kerbside Petrol Hose

GOODYEAR PH
PETROL HOSE



HARDWALL KERBSIDE PETROL hose is a premium quality steel wire braid rubber hose for all types of dispensers. Its unique construction bonds the tube to the cover through the reinforcement. This provides a homogeneous wall to stop delamination and construction failure.

DESIGN FOR LIFE

HARDWALL KERBSIDE PETROL hose is made to the highest production standards using laser technology and 100% proof testing as standard manufacturing procedure.

HARDWALL KERBSIDE PETROL hose provides safety and durability for the toughest punishment of high volume self-service applications, where safety and strength are essential.

The hardwall steel wire braid construction offers:-

- Extra strength and durability
- Failsafe electrical conductivity
- Crush, kink and cut resistant
- Low volumetric expansion for accurate metering
- Nil delamination
- Complete assemblies coupled and tested

PERFORMANCE

HARDWALL KERBSIDE PETROL hose uses compounds with excellent resistance to diesel oils, reformulated petrol and alcohol blends.

APPROVALS

HARDWALL KERBSIDE PETROL hose and assemblies meet the requirements of:- EN 1360 with branded hose and couplings.

CONSTRUCTION

TUBE:	Chemigum [®] rubber (ORS).
REINFORCEMENT:	Steel wire braid.
COVER:	Ozone resistant rubber.
COUPLINGS:	Goodyear specification mild steel plated or chromed brass

HARDWALL KERBSIDE PETROL HOSE					
I.D.		O.D.		WEIGHT	
in.	mm	in.	mm	lb/ft	Kg/m
3/8	16	1.015	25.8	0.37	0.55
1/2	19	1.240	31.5	0.52	0.78
1	25	1.485	37.7	0.66	0.98

TEMPERATURE RANGE

STANDARD HOSE:	-25 to +88C.
LOW TEMPERATURE HOSE:	available on request.

COLOURS

STANDARD:- 3/8" Green, Red, Yellow, Blue and Black.
 1/2" Black other colours available on request.
 1" Black other colours available on request.

HOSE GOODYEAR