

Two-layer soft PVC hose with embedded galvanised steel spiral with polyester yarn reinforcement, for suction and delivery of liquids.



- 
SMOOTH SURFACE

- 
FLEXIBILITY

- 
TEMPERATURE RANGE
-25 °c 60 °c

- 
CHEMICAL RESISTANCE
PVC Table

- 
CRUSHING RESISTANCE

- 
ANTI-UV

| Ø nominal mm | Ø nominal inch | Ø i.d. mm | Ø o.d. mm | vacuum 23° m/H ₂ O | working press. at 23° r.1:3 bar | working press. at 23° r.1:4 bar | bursting press. at 23° bar | bending radius mm | total thickness mm | Ø steel wire mm | spiral pitch mm | spiral direction | weight meter g/m | Segment Length m | coil length m | Availability |
|-----------------|-------------------|--------------|--------------|----------------------------------|---------------------------------------|---------------------------------------|-------------------------------|----------------------|-----------------------|--------------------|--------------------|------------------|---------------------|---------------------|------------------|--------------|
| 19 | 3/4 | 19 | 28 | 9 | 20 | 16 | 60 | 70 | 4.5 | 1 | 8.5 | right | 475 | | 60 | On demand |
| 25 | 1 | 25 | 36 | 9 | 16 | 12 | 48 | 80 | 5.5 | 1.2 | 9 | right | 680 | | 60 | In stock |
| 30 | | 30 | 40.5 | 9 | 16 | 12 | 48 | 90 | 5.3 | 1.2 | 9.5 | right | 770 | | 60 | In stock |
| 32 | 1 1/4 | 32 | 42.5 | 9 | 16 | 12 | 48 | 100 | 5.3 | 1.2 | 9.5 | right | 800 | | 60 | In stock |
| 35 | | 35 | 47 | 9 | 14 | 10 | 42 | 115 | 6 | 1.4 | 10 | right | 1100 | | 60 | On demand |
| 38 | 1 1/2 | 38 | 51 | 9 | 14 | 10 | 42 | 125 | 6.5 | 1.4 | 10.5 | right | 1200 | | 30 | In stock |
| 40 | | 40 | 52 | 9 | 14 | 10 | 42 | 130 | 6 | 1.4 | 11 | right | 1200 | | 30 | In stock |
| 45 | 1 3/4 | 45 | 58 | 9 | 12 | 10 | 36 | 140 | 6.5 | 1.4 | 11 | right | 1400 | | 30 | On demand |
| 50 | 2 | 50 | 63.5 | 9 | 12 | 10 | 36 | 150 | 6.8 | 1.6 | 11 | right | 1600 | | 30 | In stock |
| 60 | | 60 | 74 | 9 | 12 | 10 | 36 | 180 | 7 | 1.6 | 11 | right | 2000 | | 30 | In stock |
| 63 | 2 1/2 | 63 | 77 | 9 | 12 | 10 | 36 | 190 | 7 | 1.6 | 11 | right | 2100 | | 30 | In stock |
| 75 | | 75 | 91 | 9 | 12 | 10 | 36 | 190 | 8 | 2 | 13.5 | right | 2950 | | 30 | In stock |
| 76 | 3 | 76 | 92 | 9 | 12 | 9 | 36 | 210 | 8 | 2 | 13.5 | right | 2970 | | 30 | In stock |
| 80 | | 80 | 96 | 9 | 10 | 8 | 30 | 220 | 8 | 2 | 14 | right | 3020 | | 30 | In stock |
| 90 | 3 1/2 | 90 | 106.5 | 9 | 10 | 8 | 30 | 250 | 8.3 | 2 | 14 | right | 3500 | | 30 | In stock |
| 100 | | 100 | 117 | 9 | 10 | 8 | 30 | 300 | 8.5 | 2 | 14.5 | right | 4050 | | 30 | In stock |
| 102 | 4 | 102 | 119 | 9 | 10 | 8 | 30 | 300 | 8.5 | 2 | 14.5 | right | 4150 | | 30 | In stock |
| 120 | | 120 | 138 | 9 | 8 | 6 | 24 | 350 | 9 | 2.5 | 15 | right | 5430 | | 20 | In stock |
| 127 | 5 | 127 | 145 | 9 | 7 | 5 | 22 | 370 | 9 | 2.5 | 15 | right | 5950 | | 20 | In stock |
| 150 | | 150 | 169 | 9 | 5 | 3 | 15 | 480 | 9.5 | 2.5 | 15.5 | right | 7000 | | 20 | In stock |
| 152 | 6 | 152 | 171 | 9 | 5 | 3 | 15 | 480 | 9.5 | 2.5 | 15.5 | right | 7050 | | 20 | In stock |
| 200 | | 200.5 | 222 | 9 | 3 | 2.5 | 9 | 650 | 10.7 | 3 | 22 | right | 10300 | 12 | | In stock |
| 203 (**) | 8 | 203.2 | 225 | 9 | 3 | 2.5 | 9 | 650 | 10.9 | 3 | 17.5 | right | 11000 | 12 | | On demand |

* CODE 912805 VACUPRESS FLEX PLUS