


PVC hose with embedded reduced pitch galvanized steel spiral, for suction and delivery of food liquids, alcohol up to 50% proof, milk and milk products



SMOOTH SURFACE \*\*\*\*\*

FLEXIBILITY \*\*\*\*\*

ABRASION RESISTANCE \*\*\*

TEMPERATURE RANGE  
-5 °c 65 °c

CHEMICAL RESISTANCE  
PVC Table

CRUSHING RESISTANCE \*\*\*

FOR FOOD  
EU according to Declaration of Conformity.

O-PHTHALATE FREE \*\*\*\*\*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H <sub>2</sub> O	working press. at 23° r.1:3 bar	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
10	3/8	10	16.2	9	10	30	40	3.1	0.8	5.5	right	180	30	On demand
12		12	18.2	9	10	30	48	3.1	0.8	6	right	190	30	On demand
13		13	19.2	9	10	30	52	3.1	0.8	6	right	210	30	On demand
14		14	20.2	9	10	30	56	3.1	0.8	6	right	230	30	On demand
16	5/8	16	22.2	9	10	30	64	3.1	0.8	7	right	260	30	On demand
18		18.3	24.7	9	9	27	72	3.2	1	7	right	295	30	On demand
19	3/4	19	26	9	9	27	76	3.5	1	7.2	right	330	30	On demand
20		20	27	9	8.5	25.5	80	3.5	1	7.5	right	340	30	On demand
22		22	29.4	9	8.5	25.5	88	3.7	1	7.5	right	400	30	On demand
25	1	25	33	9	8.5	25.5	100	4	1	7.5	right	520	30	On demand
30		30	38.4	9	8	24	120	4.2	1	8	right	630	30	On demand
32	1 1/4	32.4	40.8	9	8	24	128	4.2	1	8	right	660	30	On demand
35		34.5	43.5	9	8	24	140	4.5	1.2	8.5	right	750	30	On demand
38	1 1/2	38	47	9	8	24	152	4.5	1.2	8.5	right	800	30	On demand
40		40.6	50.4	9	8	24	160	4.9	1.2	8.5	right	950	30	On demand
45	1 3/4	45	54.8	9	8	24	180	4.9	1.5	9.5	right	1150	30	On demand
50	2	50	60.8	9	6	18	200	5.4	1.5	9.5	right	1300	30	On demand
51		51.2	62	9	6	18	204	5.4	1.5	9.5	right	1300	30	On demand
55		55	66	9	5.5	16.5	220	5.5	1.5	9.5	right	1500	30	On demand
60		60	72	9	5.5	16.5	240	6	1.5	10.5	right	1750	30	On demand
63	2 1/2	63	75	9	5.5	16.5	252	6	1.5	10.5	right	1800	30	On demand
65		65	77.2	9	5	15	260	6.1	1.5	10.5	right	1900	30	On demand
70		70	83.4	8.5	4.5	13.5	280	6.7	1.8	12.5	right	2100	30	On demand
75		75	88.4	8.5	4.5	13.5	300	6.7	1.8	12.5	right	2250	30	On demand
76	3	76	89.4	8.5	4	12	304	6.7	1.8	12.5	right	2300	30	On demand
80		80	93	8.5	3.5	10.5	320	6.5	1.8	14	right	2500	30	On demand
89		89	102	8.5	3.5	10.5	356	6.5	1.8	14	right	2900	30	On demand
90	3 1/2	90	103	8.5	3.5	10.5	360	6.5	1.8	14	right	2900	30	On demand
100		100	116	8.5	2.5	7.5	400	8	2.5	15	right	3650	30	On demand
102	4	102	118	8.5	2.5	7.5	408	8	2.5	15	right	3700	30	On demand
105		105	121	8.5	2.5	7.5	420	8	2.5	16	right	3850	30	On demand
110		110	126	8	2.5	7.5	440	8	2.5	16	right	3950	20	On demand
120		120	136	8	2.5	7.5	480	8	2.5	16	right	4300	20	On demand
125		125	141.4	8	2.5	7.5	500	8.2	2.5	16	right	4600	20	On demand
127	5	127	143.4	8	2.5	7.5	508	8.2	2.5	16	right	4700	20	On demand
150		150	169.4	8	2	6	600	9.7	2.5	16	right	6500	20	On demand
152	6	152	171.4	8	2	6	608	9.7	2.5	18	right	6600	20	On demand
203	8	203.8	223.8	8	1.5	4.5	812	10	2.5	18	right	9000	10	On demand