


Soft PVC hose with embedded reduced pitch galvanized steel spiral for suction of food liquids.



 SMOOTH SURFACE *****


 FLEXIBILITY *****

 ABRASION RESISTANCE ***

 TEMPERATURE RANGE
-5 °C 65 °C

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE ***

 FOR FOOD
EU according to Declaration of Conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H ₂ O	working press. at 23° r.1.3 bar	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	33.5	9	5	15	60	4.25	1.2	8	right	530	60	On demand
30		30	38.5	9	5	15	70	4.25	1.2	8.5	right	620	60	On demand
32	1 1/4	32	40.5	9	5	15	75	4.25	1.2	8.5	right	650	60	On demand
35		35	44	9	4.5	13.5	80	4.5	1.4	9	right	770	60	On demand
38	1 1/2	38	47	9	4	12	90	4.5	1.4	9.5	right	810	30	On demand
40		40	49.5	9	4	12	95	4.75	1.4	9.5	right	880	30	On demand
45	1 3/4	45	55	9	3.5	10.5	110	5	1.6	10	right	1100	30	On demand
50	2	50	61	9	3.5	10.5	125	5.5	1.6	10.5	right	1270	30	On demand
60		60	72	9	3	9	140	6	1.6	11	right	1700	30	On demand
63	2 1/2	63	75	9	3	9	150	6	1.6	12	right	1770	30	On demand
75		75	88	9	2	6	200	6.5	2	13	right	2300	30	On demand
80		80	94	9	2	6	220	7	2	14	right	2600	30	On demand
90	3 1/2	90	104	9	2	6	260	7	2.5	16	right	3000	30	On demand
100		100	114	9	2	6	300	7	2.5	17	right	3350	30	On demand