


# APOLLO OIL (Cod. Ol 01)



**Tubo di colore blu in PVC-NBR, realizzato con spirale di rinforzo in PVC rigido antiurto incorporata.** Superficie interna liscia, esterna leggermente corrugata. Molto robusto e resistente a schiacciamento, abrasione, agenti atmosferici e numerose sostanze chimiche. Prodotti petroliferi (non esclusivamente petrolio). Versione antistatica con cordicella di rame disponibile su richiesta.

- Aspirazione e mandata di olii minerali, lubrificanti, carburante grezzo (nafta, diesel) e come linea di ritorno su circuiti idraulici.


**Blue PVC-NBR hose manufactured incorporating a spiral reinforcement of anti-shock rigid PVC.** Inside surface smooth, light corrugated outside. Very strong and resistant to crushing, abrasion, atmospherical agents and most chemicals. Petrol base products(not solely petrol). On request, It can be manufactured in the antistatic version with copper wire.

- Suction and delivery of mineral oils, lubricants, crude fuel (naphta, diesel oil) and as a return line in hydraulic systems



Spirale in PVC rigido antiurto / Anti-shock rigid PVC spiral

Tubo in PVC/NBR / PVC/NBR hose



## Scheda tecnica / Technical data

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo	Vol.
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.	Vol.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
0101020000000	20*	3,2	3,5	290	7,0	21	10	80	50	0,069
0101025000000	25*	3,4	3,8	390	6,0	18	10	100	50	0,083
0101025400000	25,4*/1"	3,4	3,8	400	6,0	18	10	100	50	0,084
0101032000000	31,8*/1.1/4"	4,0	4,4	590	6,0	18	10	130	50	0,130
0101038000000	38,1*/1.1/2"	3,9	4,5	670	5,0	15	10	155	50	0,203
0101040000000	40*	3,9	4,5	700	5,0	15	10	160	50	0,212
0101052000000	50,8*/2"	4,3	4,9	970	4,0	12	10	200	50	0,262
0101055000000	55*	4,5	5,1	1100	4,0	12	9	220	50	0,376
0101060000000	60*	4,7	5,4	1270	4,0	12	9	260	50	0,408
0101063000000	63,5*/2.1/2"	4,8	5,5	1370	4,0	12	9	260	50	0,429
0101070000000	70*/2.3/4"	4,9	5,6	1490	3,0	9	9	350	50	0,585
0101076000000	76,2*/3"	5,0	5,7	1660	3,0	9	9	310	50	0,631
0101080000000	80*	5,2	6,0	1810	3,0	9	9	400	50	0,795
0101090000000	90*	5,4	6,3	2110	3,0	9	9	360	30	0,591
0101102000000	102*/4"	6,0	7,1	2680	3,0	9	8,5	410	30	0,837
0101127000000	127*/5"	6,4	7,5	3510	2,5	7,5	8	510	30	1,091
0101152000000	152,4*/6"	7,4	8,7	4930	2,0	6	8	610	20	1,358
0101203000000	203,2*/8"	10,9	12,9	10010	1,5	4,5	7	850	10	1,832

\*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / \*Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity