## Specification for Product Code

## Odourless Kerosene ODKEGEN

Other chemical names

Standard Specifications				
Properties	Units	Methods	Specification Min Max	
Appearance	-	Visual	Clear and free from suspended matter	
Purity	% (w/w)	GC/ATSM 3545	Not recorded	
Assay	% (w/w)	-	Not recorded	
Density at 15 °C (Approx 60°F)	kg/L	ASTM D 4052/ASTM D 3505	.80	0.835
Density at 20 °C	kg/L	ASTM D 4052	Not recorded	
Distillation range	*c	ASTM D 1078/IP 195/ASTM D 850	Not recorded	
Initial Boiling Point (IBP)	*c	ASTM D 1078/ASTM D 86	185	
Dry Point (DP)	*c	ASTM D 1078/ASTM D 86		280
Flash point	*c	EN ISO 13736/ASTM D 93/IP 170	72	
Colour (Pt-Co/Hazen)	Pt-Co	ASTM D 1209	Not recorded	
Colour (Saybolt)	-	ASTM D 156	Min + 29	
Water content	% (w/w)	ASTM D 1364	Not recorded	
Water miscibility	% (w/w)	ASTM D 1722	Not recorded	
Acidity as Acetic Acid - (CH₃COOH)	% (w/w)	ASTM D 1613	Not recorded	
Acidity mg. NaOH/100 ml	-	ASTM D 847	Not recorded	
Refractive index at 20 °C	-	ASTM D 1218	Not recorded	
Aromatics	% (w/w)	UOP 495		0.1
Non-aromatics	% (v/v)	ASTM D 2360	Not recorded	
Free from SH <sub>2</sub> & SO <sub>2</sub>	-	ASTM D 853	Not recorded	
Odour	-	IWG IH 90-2	Not recorded	
Residue on evaporation	% (w/w)	ASTM D 1353/IBES 07/ASTM D 1296	Not recorded	
Additional Specifications				
None for this product	-	-		-

Where multiple methods are listed, the testing method may vary between batches. There may not be data for all tests listed.

This data is correct and reliable to the best of our knowledge and provided in good faith but without guarantee. It is the responsibility of the customer to ensure that the product is suitable for their end use and to ensure its correct handling.

Please refer to the product Safety Data Sheet for health, safety and environmental information, or contact us for further information.