SPECIFICATION SHEET

UN 1 TIGHT HEAD STEEL DRUM

CARRICK

7 LITRES

A steel tight head drum manufactured in accordance with the UN packaging specification, and satisfies the provisions of the packaging and packaging waste directive 94/62/EC.

Tested for Packaging Groups 1, 11, 111.

Closure

G2 Tri-Sure steel closure Closing Torque G2= 25 N/m

Additional Specification

• Side Seam - Welded

• End Seams - Double Seamed & Solutioned

• Rolling Hoops - None

• Handle - Wire Drop handle

Internal Finish - Plain/ Epoxy Phenolic Coating

External Finish - Stoving Enamel



Volume	Steel Plate Thickness (mm)			Weight	UN Approval	
7 Litre Nominal	Top End	Body	Bottom	1.6 kg		
	0.6mm +/05mm	0.6mm +/05mm	0.6mm +/05mm	+/- 5%	1A1/X/400/**/GB/5322	

To test levels of	The packaging is approved as provided in the relevant transport rule, to contain liquids of		
Drop Height (m)	1.8	packaging group	density (d)
Leakproofness (kPa)	30	1	1.2
Stacked at 3m with RD(d)	1.8	11	1.8
Internal Pressure (kPa)	400	111	1.8

Qty Per	Pallet	Shrink	Strap	Pallet	Layer	Foam
Pallet	Size	Wrap		Hood	Pad	Wrap
175	1100mm x 1100mm	Yes	Optional	Optional	Optional	Optional

N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained. Additional UN information can be found on www.vca.org.gov Information on terms & conditions can be found on www.jamesgcarrick.com

This document is uncontrolled when printed.

James G Carrick & Co Ltd 450 Petershill Road Springburn Glasgow G21 4PB Issue date 1st August 2011

Tel +44 141 558 6008 Fax +44 141 557 0318 e mail sales@jamesgcarrick.com

Issue No 1