

# 915133 POLIPO 15 BAR OIL



Soft PVC hose with POLYURETHANE (PU) underlayer with polyester yarn reinforcement and PU adhesive middle layer, for pressurized transfer of oil, diesel oil, bio diesel urea (ISO 22241).



SMOOTH SURFACES

\*\*\*\*\*



FLEXIBILITY

\*\*\*



ABRASION RESISTANCE

\*\*\*



TEMPERATURE RANGE

-10°C +60°C  
14°F +140°F



CHEMICAL RESISTANCE

PU table



CRUSHING RESISTANCE

\*\*\*

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	WORKING PRESSURE 60°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	bar	m	
3/4	19	26	3.5	350	65	15	10	6	45	50	ON DEMAND
1	25	35	5	640	100	15	10	6	45	50	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.