

INOX 3/5/7/12 ROUND FILTER HOUSINGS



Product Specification

-  316L STAINLESS STEEL POLYCOATED
-  120°C
-  10 BAR
-  sfwt.eu/sfh-spc
-  PDFs
- 
- 

Ordering Details

Product Code	Material	Cartridge Quantity	Cartridge Size (")	Port Size (")	Gauge Ports	Mounting Tabs
SFH	SPC = Stainless Steel Polycoated	3	10, 20, 30, 40	2 BSPM	GP	MT
		5	20, 30, 40			
PFH		7	20, 30, 40	3 DN80		

- SPC - - - - GP - MT
 e.g. SFH-SPC-5-10-2-GP-MT



Packaging	3 Round				5 Round				7 Round				12 Round			
	10"	20"	30"	40"	10"	20"	30"	40"	20"	30"	40"	20"	30"	40"	30"	40"
	11 kg	16 kg	19 kg	23 kg	12 kg	17 kg	20 kg	25 kg	26 kg	29 kg	33 kg	42 kg	46 kg			

Features & Information

- The PED compliant and DWI approved SPECTRUM multi-round housing secures with a v-band clamp, as standard, for easy opening and closing. A swing-bolt closure option is available, changing the code from SFH to PFH
- Universal cartridge adaptors securely hold 222 or DOE cartridges
- Gauge ports allow two gauges to be fitted to easily read differential pressure
- Drain ports allow for quick and easy cartridge change-outs
- Protective polycoat finish
- Buna-N seal as standard

Premier (PFH) housings have the added security of a swing-bolt closure where the head remains attached to the housing allowing simple tool free cartridge change-outs



Adjustable top plate takes DOE or 222/Fin or 222/closed end cartridges



Universal cartridge adaptor securely holds 222 or DOE filter cartridges

Compatible End Caps



Standard DOE Cartridges
e.g. Wounds, Spun, Pleated

A = Open End

E = 222

G = Closed Recessed End

H = Fin