

INOX MULTI ROUND BAG HOUSINGS

HOUSINGS: STAINLESS STEEL BAG



Product Specification



316L STAINLESS STEEL POLYCOATED



149°C



10



sfwt.eu/pbh-spc



Ordering Details

Product Code	Material	No. of Bags	Bag Size	Flange Size (")
PBH	SPC = Stainless Steel Polycoated	2	2	3 DN80
		3		4 DN100
		4		
		5		
		6		
		8		8 DN200

- - - -

e.g. PBH-SPC-5-2-4

Packaging	2 bag	3 bag	4 bag	5 bag	6 bag	8 bag
	1 at 105kg	1 at 135kg	1 at 170kg	1 at 265kg	1 at 300kg	1 at 450kg

Features & Information

- PED compliant, DWI approved SPECTRUM PBH multi-cavity bag housings are the perfect solution for high flow rate applications up to 3,600 lpm - flow rate data available online
- Heavy duty swing-bolt closure and cover lifting davit arm assembly for simplified handling
- 304L legs can be bolted to the floor for safety and security
- Basket hold-down device ensures that the multiple baskets won't move under high flow conditions
- Housing comes with ¼" gauge ports and includes 0-6.9 bar stainless steel pressure gauge
- Buna-N V-seal as standard