

OILOUT - 99

WATER TREATMENT: CARBON



Product Specification



RESIN IMPREGNATED FELT



70°C



sfwt.eu/srif



Ordering Details

Product Code	Lengths (")	End Caps	Seal	Average Oil Removal (grams)
SRIF	9 3/4	AA ES	BUNA = B	360
	20			720
	30			1,080
	40			1,140
	9 3/4BB			1,290
	20BB			2,580

SRIF — [] — [] B
e.g. SRIF-20-AAB

Packaging	9 3/4"	20"	30"	40"	9 3/4"BB	20"BB
	15 at 4kg	15 at 7kg	15 at 10kg	15 at 13kg	6 at 4kg	6 at 8kg

Features & Information

- Effectively removes dissolved and dispersed hydrocarbons efficiently from water, absorbing three times its own weight before change-out is required
- As the cartridge becomes exhausted, flow is not affected and no hydrocarbons are released
- Removes up to 99% of hydrocarbons with each 10" cartridge having a capacity of 360g of hydrocarbon in standard size and 1290g in its large diameter format
- Constructed from resin impregnated felt, polypropylene core and end caps, protected by polyethylene netting
- Multiple end cap options in standard and large diameter configurations ensures the OilOut-99 is suitable for large scale industrial to small commercial applications