

TODO® PTC - Safety Pressure Tight Cap

The TODO® PTC is specifically designed to enhance operator safety and containment security in chemical and gas transport.

Designed in close collaboration with leading chemical and gas companies, the PTC offers safety and operational benefits beyond those offered by existing closure technologies.

Should the possibility of an upstream closure leakage occur, the PTC provides identification of a system pressure and will hold this pressure until the problem can be safely resolve

Should the operator still choose to remove the cap it will reduce the static pressure to zero thus preventing the forceful expulsion of the transfer media.



Approved as third closure for category II product.

Features

- Pressure indicator.
 - This feature alerts the operator to the presence of a pressure above 1.0 bar behind the cap and possible failure of upstream closure.
- Automatic depressurization.
 - Reduces any static pressure upstream of the cap upon operation.
 - Any other sealing cap or flange may allow removal under pressure with potentially serious consequences for the operator.
 - Removes the possibility of disconnecting the cap whilst under pressure.
- Customs / tamper seal feature.
 - The cap operating mechanism will accept all commonly used wire and plastic custom seals.
- Automatic locking.
 - The PTC locks automatically in either direction but requires a deliberate action to disconnect.
- Certified closure.
 - The PTC is certified as a full second or third closure depending on the application. The cap can be used to replace other closure methods such as valves.
- Manually lockable.
 - The PTC can be manually locked using a padlock.

Certificates / Approvals

- VdTÜV type approval, mark TÜ.AGG.162-93 towards ADR, RID, IMDG and VDI-rules 2440, part 3.3.1.3.
- CE-marked, European directives 97/23/EC (PED) and 94/9/EC (ATEX) compliant.
- TDT approval, mark TDT-UW-30/09 towards ADR/RID in Poland.
- Manufactured under EN ISO 9001:2000.
- Certified towards ISO 14001:2004 and OHSAS 18001:2007.
- Manufactured towards EN 13480 and EN 13445.



Technical Details

Sizes: 2" (DN 50), 3" (DN 80) and 4" (DN 100).

Materials: 316L stainless steel.

Seals: FKM (Viton®), EPDM, Nitrile, various Perfluorelastomers.


Working pressure: PN 25
Test pressure: PN 37.5

Compatibility: Tank unit caps according to NATO STANAG 3756.

Viton® is registered trademarks of DuPont Performance Elastomers.

Safety Pressure Tight Cap Size Range







3" (DN 80) PTC



4" (DN 100) PTC

Applications



Approved as second closure on the top of tanks.





TODO AB

Box 33, Industrigatan 2-4 · S-545 21 Töreboda · Sweden Phone +46 506 19940 · Fax : +46 506 19944

EMCO WHEATON UK Limited

Channel Road · Westwood Industrial Estate Margate, Kent CT9 4JR · UK Phone +44 1843 221521 · Fax +44 1843 295444

EMCO WHEATON GmbH

Emcostraße 2-4 · 35274 Kirchhain · Germany Phone +49 6422 84-0 · Fax +49 6422 5100

EMCO WHEATON USA, INC.

9111 Jackrabbit Road · Houston, Texas 77095 · USA Phone +1 281 856-1300 · Fax +1 281 856-1325

EMCO WHEATON Corp.

2480 Bristol Circle · Oakville, Ontario L6H 5S1 · Canada Phone +1 905 8298619 · Fax +1 905 8298620

GARDNER DENVER Inc.

306 Middletown Park Place, Suite D Louisville, KY 40243 · USA Phone +1 502 489 3884 · Fax +1 502 489 3882

www.todo.se www.emcowheaton.com

assist@todo.se assist@emcowheaton.com

GARDNER DENVER FRANCE SA

Immeuble Le Miroir, 15-17, Boulevard du G^{al.} de Gaulle 92120 Montrouge · France Phone +33 146 1241-41 · Fax +33 146 1241-59

EMCO WHEATON ASIA PACIFIC

21 - 5F · IOI Business Park · Bandar Puchong Jaya 47100 Puchong Selangor · Malaysia Phone +603 8075-7500/7900 · Fax +603 8075-4100

GARDNER DENVER INTERNATIONAL LTD.

PO Box 30804 · Diraz, Manama · Bahrain Phone +973 17813187 · Fax +973 17813186

EMCO WHEATON GmbH

Branch Office CEE
Blue Danube Park, Objekt 60 · 2100 Korneuburg Austria
Phone +43 2262 64281-0 · Fax +43 2262 6428120

EMCO WHEATON GmbH Sp.z.o.o.

Oddzial w Polsce ul. Królewska 57 · 30-081 Kraków · Poland Phone +48 12 2934308 · Fax +48 12 2934309

EMCO WHEATON Regional Sales Office

PO Box 468 · Cross Lane, Tong, Bradford · West Yorkshire BD4 OSU · UK
Phone +44 1274 683131 · Fax +44 1274 651006