

Part Number: ZVF 50 JET.3 SIC ER 583 GKG38 EKG1200



© ELAFLEX HIBY, Hamburg / Germany

<https://nozzleconfigurator.elaflex.co.uk/NON AUTO AIR/3484/24866/24870/24880/24878/24936/24896/24961/24945/Product11.html>

Nozzle Type	ZVF 50 Manually operated nozzle DN 50 Manual aviation fuelling nozzle without automatic shut-off function for overwing service. For AVGAS and JET-fuels. Max. flowrate 400 l/min. (85 IGM - higher flowrates are possible). Size DN 50
Body	ZVF 50 JET For JET fuels
Hose Inlet	DG 50.3 AF AI black 1½" BSP female Easy-rotating swivel. For petroleum based products, i.e. aircraft refuelling (ZVF 50).
Spout Connection	Screw-In-Connection Standard type Screw-In-Connection (SIC) for spouts.
L-Type	Standard Suitable for pressure service with a pump.
Sight Glass	Without sight glass Without
Spout	DN 38 Spout ID 38 mm, OD 44 mm. max. 400 l/min.
Dust Cap Assembly	With GKG 38 Dust Cap Assembly GKG 38 Dust cap assembly. Cap NBR, chain and spring brass and bronze.
Ground Cable Assembly	With EKG 1200 Ground Cable Assembly EKG 1200 With brass clamp, and plastic coated steel wire.

1200 mm standard length.
Assembly is mounted by Elaflex.

PDF Documents

-  Page 541a-d (ZVF 50)
-  Page 363-364 (DG 50.3 AF AI black)

Contact:

ELAFLEX Limited
Riverside House,
Plumpton Road
Hoddesdon, Herts EN11 0PA
United Kingdom
Phone No.: +44 (0)1992 452 950
Internet: www.elaflex.co.uk